

KNOWLEDGE BASE · PUBLIC DOCUMENT

Testing IMAP, POP3 and SMTP by hand with openssl s_client: a guide for technical users

E-mail

CODE

RLX-MZ-KB-2144

VERSION

v2026.10.16

COUNTRY · LANGUAGE

Mozambique · English

Interweb Mozambique

RLX Holdings, S.A. · Group RLX Holdings

Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

<https://www.meu.interweb.co.mz/knowledgebase/2144>



This article is for technical users with a command line (Linux, macOS, or Windows with OpenSSL). **The short answer:** `openssl s_client` opens an encrypted connection to the server and lets you type the protocol commands by hand. That separates a server problem from a program problem: if it works by hand, the server, the port and the password are right, and the fault is in the program settings.

The replies you will see

Protocol	It worked	It failed
IMAP (port 993)	The line ends in OK , after the tag you typed (a1, a2...).	NO (the server refused, the password for example) or BAD (the command is badly written).
POP3 (port 995)	+OK	-ERR , followed by the reason.
SMTP (port 465 or 587)	2xx codes (220 greeting, 235 authenticated, 250 accepted) and 354 (go ahead and type the message).	4xx temporary, 5xx final: 535 is a rejected password, 550 is a refused recipient or sender.

IMAP by hand

1

Connect. Use your own domain: `openssl s_client -connect mail.yourdomain:993 -crlf -quiet` The server answers with a line starting * **OK**.

2

See what the server can do, then log in. Every IMAP command starts with a tag of your choosing: `a0 CAPABILITY`
`a1 LOGIN you@yourdomain "the-password"` If the password has spaces or quotes, the simplest thing is to test with a temporary one.

3

List the folders and open the Inbox: `a2 LIST "" "*"`
`a3 SELECT INBOX` SELECT tells you how many messages there are (EXISTS).

4

Read the header of the first message without marking it as read (PEEK is what avoids the flag): `a4 FETCH 1 (FLAGS BODY.PEEK[HEADER.FIELDS (FROM SUBJECT DATE)])`

5

Leave: `a5 LOGOUT`

POP3 by hand

1

Connect and log in: `openssl s_client -connect mail.yourdomain:995 -crlf -quiet`
`USER you@yourdomain`
`PASS the-password`

2

Count and list the messages: `STAT`

`LIST`

`UIDL` `STAT` gives the number of messages and the total size; `UIDL` gives the unique identifier of each one, the same one your program uses to know what it already downloaded.

3

Leave with `QUIT` . **Do not use** `DELE` in a test: it marks the message for deletion, and `QUIT` deletes it for good.

SMTP by hand

1

Prepare the username and password in base64 (AUTH PLAIN format).

`read -s` asks for the password without showing it or saving it in the history: `read -s P`

```
printf '\0%s\0%s' 'you@yourdomain' "$P" | base64
```

2

Connect. Over 465 (SSL/TLS) or 587 (STARTTLS): `openssl s_client -`

```
connect mail.yourdomain:465 -crlf -quiet
```

```
openssl s_client -starttls smtp -connect mail.yourdomain:587 -  
crlf -quiet
```

3

Introduce yourself, log in and send to an address of your own:

```
EHLO test
```

```
AUTH PLAIN the-base64-text-from-step-1
```

```
MAIL FROM:<you@yourdomain>
```

```
RCPT TO:<another-address-of-yours@example.com>
```

```
DATA
```

```
Subject: test by hand
```

```
This is a test.
```

```
.
```

QUIT The line holding a single dot ends the message; the server answers 250 and the message goes into the queue.

4

Read the EHLO reply: the list of 250 lines shows the extensions the server accepts (AUTH, SIZE, STARTTLS...). If AUTH is missing, the connection is not in the right mode to log in.

What you type stays on screen. The password shows in clear in the terminal window, and in SMTP it goes as base64, which is no encryption at all: anyone can decode it. Run these tests on your own computer, close the terminal afterwards, and never paste the output into a support ticket or a forum without removing the password and the AUTH line.

Without -quiet, s_client reads some letters as commands. A line starting with a capital **R** (such as RCPT TO) renegotiates the connection, and one starting with **Q** closes it. With `-quiet` that does not happen; alternatively, type the SMTP commands in lower case, which the protocol accepts.

The test by hand works but your program still fails? Tell us the program, the port and the error message, without the password.

[Open a support ticket](#)

SEE ALSO

[SMTP ports 465, 587 and 25: SSL, STARTTLS and which one to use](#)

[Which ports are open, and why your integration hangs without an error](#)

[POP or IMAP: which to choose, and what you lose by picking wrong](#)

[IMAP folders, flags and IDLE: how push e-mail works and why a folder lags behind](#)

[How an e-mail travels: SMTP to the MX server, then IMAP or POP to the reader](#)

[Why your e-mail is not sending or receiving](#)



Online version of this document

Interweb is a leading internet services company, with a mission to help businesses to be born and prosper through technology.

2020

FOUNDED

37,000+

CLIENTS

130+

SIGN-UPS A DAY

Interweb Mozambique

RLX Holdings, S.A. • Group RLX Holdings

TAX ID (NUIT)	401 191 607
LEGAL ENTITY NO. (NUEL)	105 045 974
ECONOMIC ACTIVITY CODE (CAE)	62022
REGISTERED OFFICE	Bairro 7 de Setembro Vilankulo 1304 • CEP 0411-02, Inhambane, Mozambique
CONTACT	info@interweb.co.mz • +258 84 635 1111 • +258 86 635 1111 • www.interweb.co.mz
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed