interweb

Generated on 13/11/2026 19:26

KNOWLEDGE BASE · PUBLIC DOCUMENT

Testing an SMTP credential before going live: a test e-mail from the command line

E-mail


CODE	VERSION	COUNTRY · LANGUAGE
RLX-MZ-KB-2542	v2026.11.13	Mozambique · English

Interweb Mozambique
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.interweb.co.mz/knowledgebase/2542

Testing an SMTP credential before going live: a test e-mail from the command line

E-mail Created on **November 13, 2026** 2 min read



This article is for people with access to a command line (a VPS, the cPanel terminal when the account has SSH, or your own computer). **The short answer:** before you put the credential into the program, send a test e-mail with it **from the same machine** the program will run on. If the test works, the credential, the port and the network are fine, and any error that shows up later is in the program settings.

With swaks

swaks is a small tool made for testing SMTP; install it from your distribution package manager. The first line asks for the password without showing it and without leaving it in the history:

```
read -s SMTP_PASSWORD
swaks --server SMTP_HOST --port 587 --tls \
--auth-user SMTP_USER --auth-password "$SMTP_PASSWORD" \
--from no-reply@asuaempresa.co.mz --to you@example.com
```

For port 465, replace `--port 587 --tls` with `--port 465 --tlsc`. swaks shows the whole conversation with the server, line by line.

With Python, nothing to install

```
python3 - <<'END'
import getpass, smtplib
s = smtplib.SMTP("SMTP_HOST", 587); s.starttls()
s.login("SMTP_USER", getpass.getpass("Password: "))
s.sendmail("no-reply@asuaempresa.co.mz", ["you@example.com"], "Subject: Test\r\n\r\nSMTP
Relay test")
s.quit()
END
```

Reading the answer

What you see	Means	What to do
A reply starting with 250 at the end	The relay accepted the e-mail.	Check it in the Email Center log and in your mailbox.
Authentication error (code 535)	Wrong username or password, or a revoked credential.	Check what you copied, or create a new credential.
Sender refused	The sender domain is not verified.	Use an address on the verified domain.
It hangs with no answer	The port is blocked on this machine network.	Try 465. See **which ports are open**.

Never type the password straight into the command.
It stays in the shell history and, on a shared server, can show up in the process list. Both examples above ask for it without showing it.

To see the SMTP conversation command by command, by hand, there is **the openssl s_client test**.

NEED A HAND?

Test failing and you cannot see why? Open a ticket with what the command showed, without the password.

Open a support ticket →

SEE ALSO

- **SMTP Relay not sending: connection, TLS, login, sender and recipient problems, one by one**
- **Testing IMAP, POP3 and SMTP by hand with openssl s_client: a guide for technical users**
- **Which ports are open, and why your integration hangs without an error**
- **Sending through SMTP Relay from Node.js and Python: Nodemailer and smtplib, with STARTTLS**

The program says sent, the customer got nothing: finding SMTP e-mails in the Email Center log

interweb

Interweb Mozambique

RLX Holdings, S.A. · Group RLX Holdings

TAX ID (NUIT)	401 191 607
LEGAL ENTITY NO. (NUEL)	105 045 974
ECONOMIC ACTIVITY CODE (CAE)	62022
REGISTERED OFFICE	Bairro 7 de Setembro Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique
CONTACT	info@interweb.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.interweb.co.mz
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-MZ-KB-2542 · v2026.11.13 · Generated on 13/11/2026 19:26