interweb

Generated on 13/11/2026 19:33

KNOWLEDGE BASE · PUBLIC DOCUMENT

The API Playground: trying a real request from your browser, step by step

WhatsApp & APIs

CODE	VERSION	COUNTRY · LANGUAGE
RLX-MZ-KB-2718	v2026.11.13	Mozambique · English

Interweb Mozambique
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.interweb.co.mz/knowledgebase/2718

The API Playground: trying a real request from your browser, step by step

WhatsApp & APIs Created on **November 13, 2026** 2 min read



The short answer: the Playground makes **real API requests from your browser**, with nothing to install. You pick the operation, fill in the request, send it and see the answer. At the same time it shows the **request code** in curl, PHP, Python and JavaScript, which follows what you type.

Two ways to open it

Where	How it works
On the Playground page	Lists every operation, with a "Search operations" box. Pick one and the panel opens on that same page.
Inside each operation	On the area pages, every operation has a Playground button that opens the same panel without leaving the page.

Step by step

1. **Start with an operation that needs no key:** `GET /v1/ping` confirms the API is answering. It is the best first test.

2. **Type your key**, when the operation asks for one, in the "API key" field. To practise, use a `sandbox_` key. The Show button lets you see what you typed.

3. **Fill in the parameters.** The required ones are marked.

4. **Choose the headers.** `Accept-Language` sets the language of the messages; "Add a header" adds others.

5 **Write the body in JSON**, on operations that have one. The page tells you whether the JSON is valid before you send it.

6 **Click Send request**, or press **Ctrl+Enter**.

7 **Read the answer:** status, time, remaining requests, body and headers. See **how to read the answer**.

From a browser, the API only accepts four headers:
`Authorization`, `Content-Type`, `Idempotency-Key` and `Accept-Language`. Any others you add go only into the generated code, for use in your own program.

Why it works here and not on your website

Browsers can only call the API from the documentation. The pages of your own website cannot use the key directly, and that is a good thing: the key would be visible to anyone who opened the page. In your project, the call is made on the server. The reason is explained in **CORS errors**.

The Playground needs JavaScript.
Without it, each operation opens its explanation on the area page. Taking care of your key: **your key in the Playground**.

RECOMMENDED

Make your first request now: the ping needs no key.

Open the Playground →

SEE ALSO

- **Your key in the API Playground: where it stays, why sandbox_ first, and the prod_ warning**
- **Reading the API Playground answer: status, time, remaining requests, headers and history**
- **Code examples in our API docs: curl, PHP, Python and JavaScript, ready to copy and adapt**
- **A reading path through our API docs: from the first request to a finished integration**
- **CORS error between your front end and your API: how to fix it**

interweb

Interweb Mozambique

RLX Holdings, S.A. · Group RLX Holdings

TAX ID (NUIT)	401 191 607
LEGAL ENTITY NO. (NUEL)	105 045 974
ECONOMIC ACTIVITY CODE (CAE)	62022
REGISTERED OFFICE	Bairro 7 de Setembro Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique
CONTACT	info@interweb.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.interweb.co.mz
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-MZ-KB-2718 · v2026.11.13 · Generated on 13/11/2026 19:33