interweb

Generated on 28/11/2026 22:08

KNOWLEDGE BASE · PUBLIC DOCUMENT

# Using your agent in n8n or another OpenAI-compatible app: agent/ as the model

Agents Through the API

| CODE | VERSION | COUNTRY · LANGUAGE |
| --- | --- | --- |
| RLX-MZ-KB-3064 | v2026.11.28 | Mozambique · English |

**Interweb Mozambique**
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.interweb.co.mz/knowledgebase/3064

# Using your agent in n8n or another OpenAI-compatible app: agent/ as the model

Agents Through the API Created on **November 28, 2026** 2 min read



An app that talks to OpenAI in the chat format also talks to your agents. It needs three things: our base address, your key and, in place of the model, `agent/` followed by the agent id.

## The three fields

| Field | What to enter |
|---|---|
| **Base address (Base URL)** | `https://api.interweb.co.mz/v1` |
| **Key (API Key)** | An **API Center** key with `ai:read` and `ai:write` |
| **Model** | `agent/` and the id, copied from Use through the API |

Agents are used in the chat, `POST /v1/chat/completions`. If the app has an option to use another format, such as the Responses API, leave it off.

## In n8n

1. Create the OpenAI credential with our address in Base URL, as in **using All in One AI in n8n**.
2. In the OpenAI Chat Model node, choose that credential. In the model field, switch from From List to ID and type `agent/...`.
3. Leave the Use Responses API option off.

You can also use the HTTP Request node, with `POST` to `https://api.interweb.co.mz/v1/chat/completions`, the key in Bearer Auth and this JSON body:

```
{
  "model": "agent/7c1e9a42-b35d8f06-a2c4e719-5d0b3f8e",
  "messages": [
    { "role": "user", "content": "Which services do you offer on Saturdays?" }
  ],
  "max_tokens": 400
}
```

Or **our n8n node**, with the AI operation Chat with a text model: in the model, type the agent id.

## What the app can change

The model is always the agent's. The app's maximum tokens and temperature can lower the agent's, but never go above them. If the app has a system instructions field, leave it empty whenever you can: the agent's instructions and knowledge already go with every request, and extra text only spends tokens.

## Testing

With a `sandbox_` key, the answer is always "Resposta de teste (sandbox).": it confirms the address, the key and the id without spending. If the app tests the credential with the model list, your agents show up there first, with the id `agent/...`.

A `404 model_not_found` means a wrong id or an agent from another account; a `409 agent_paused`, a paused agent. See **agent errors through the API**.

RECOMMENDED

Want your agent in your n8n workflows? See All in One AI.

See All in One AI →

SEE ALSO

- **Using All in One AI in n8n: the OpenAI credential with our address, or the HTTP Request node**
- **Any app that accepts an OpenAI-compatible address: the base URL, the key and the model id**
- **Our n8n node: domains, DNS, VPS, SMS, e-mail and AI in your workflows**
- **Agent errors through the API: agent_paused and model_not_found**
- **All in One AI**

interweb

## Interweb Mozambique

**RLX Holdings, S.A. · Group RLX Holdings**

| | |
|---|---|
| TAX ID (NUIT) | 401 191 607 |
| LEGAL ENTITY NO. (NUEL) | 105 045 974 |
| ECONOMIC ACTIVITY CODE (CAE) | 62022 |
| REGISTERED OFFICE | Bairro 7 de Setembro<br>Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique |
| CONTACT | info@interweb.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.interweb.co.mz |
| OPENING HOURS | Monday to Friday - 08 AM to 04 PM<br>Saturday & Sunday - Closed |

Online version of this document

RLX-MZ-KB-3064 · v2026.11.28 · Generated on 28/11/2026 22:08