interweb

Generated on 28/11/2026 22:10

KNOWLEDGE BASE · PUBLIC DOCUMENT

# Setting up the MCP server with aio mcp install for Claude Code, Codex and Cursor

The aio Command

| CODE | VERSION | COUNTRY · LANGUAGE |
| --- | --- | --- |
| RLX-MZ-KB-3088 | v2026.11.28 | Mozambique · English |

**Interweb Mozambique**
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.interweb.co.mz/knowledgebase/3088

# Setting up the MCP server with aio mcp install for Claude Code, Codex and Cursor

The aio Command Created on **November 28, 2026** 2 min read



The MCP server gives your coding agent tools to create images, videos and voice. If you already have `aio` installed with your key, you do not need to copy anything from the docs: `aio mcp install` shows the setup for each tool, already with the `https://api.interweb.co.mz/mcp` address and the `interweb-ai` name.

## The three commands

```
aio mcp install claude
aio mcp install codex
aio mcp install cursor
```

Each one shows the command or the config block for that tool, with the key hidden. Use `--show-key` if you need to see the full key.

## In Claude Code

`aio` shows the `claude mcp add` command and only runs it if you confirm. With `--yes`, it runs without asking:

```
aio mcp install claude --yes
```

Then check with `claude mcp list` or, inside Claude Code, with `/mcp`. The server should show as connected.

## In Codex and Cursor

Here `aio` shows the block to add to the config file: `~/.codex/config.toml` in Codex; `~/.cursor/mcp.json` (all projects) or `.cursor/mcp.json` (one project) in Cursor. In both, the key comes from the `AIO_API_KEY` variable.

> **Codex and Cursor do not read the key saved by aio.**
> `Aio auth login` saves it in the settings file of `aio` itself. The Codex and Cursor block reads the `AIO_API_KEY` variable, which must exist when the tool opens. Set it and open the tool again.

On Linux and macOS:

```
export AIO_API_KEY="prod_..."
```

On Windows, `setx AIO_API_KEY "prod_..."` saves the variable for the windows you open afterwards. Close the terminal and the tool, then open them again.

In Codex, check with `codex mcp list` or with `/mcp`. The block in our docs has `tool_timeout_sec = 120`, which gives generations time. If the block you copied does not have it, add it to the same section: by default, Codex gives up after 60 seconds (**Codex docs**). In Cursor, check in the list of MCP servers that the server is enabled and the tools show up (**Cursor docs**).

## Other tools

`aio mcp install` covers Claude Code, Codex and Cursor. For Windsurf and Cline, see **the file for each one**. For Claude Desktop, **the custom connector**. For ChatGPT, **the plugin, step by step**.

In Claude Code you can also sign in with your account, with no key at all. See **the MCP server in Claude Code without a key**.

RECOMMENDED

Want images, videos and voice inside your agent? See All in One AI.

See All in One AI →

SEE ALSO

- The All in One AI MCP server: images, video and voice inside Claude Code, Codex and ChatGPT
- The MCP server in Claude Code without a key: signing in with your account
- The All in One AI MCP server in Cursor, Windsurf and Cline: the file for each one
- The MCP server tools one by one: list_models, generate_image, chat, web_search and others
- All in One AI

interweb

## Interweb Mozambique

**RLX Holdings, S.A. · Group RLX Holdings**


| | |
|---|---|
| TAX ID (NUIT) | 401 191 607 |
| LEGAL ENTITY NO. (NUEL) | 105 045 974 |
| ECONOMIC ACTIVITY CODE (CAE) | 62022 |
| REGISTERED OFFICE | Bairro 7 de Setembro<br>Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique |
| CONTACT | info@interweb.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.interweb.co.mz |
| OPENING HOURS | Monday to Friday - 08 AM to 04 PM<br>Saturday & Sunday - Closed |


Online version of this document

RLX-MZ-KB-3088 · v2026.11.28 · Generated on 28/11/2026 22:10