interweb

Generated on 28/11/2026 22:13

KNOWLEDGE BASE · PUBLIC DOCUMENT

Claude Code asks for a claude-sonnet model: which model answers and what you pay

Claude Code

CODE	VERSION	COUNTRY · LANGUAGE
RLX-MZ-KB-3118	v2026.11.28	Mozambique · English

Interweb Mozambique
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.interweb.co.mz/knowledgebase/3118

Claude Code asks for a claude-sonnet model: which model answers and what you pay

Claude Code Created on **November 28, 2026** 2 min read



Sometimes Claude Code asks for a model by its own name, such as `claude-sonnet-...`, instead of the catalogue id. It happens when `ANTHROPIC_MODEL` is not set, and also when a function or a subagent uses one of the Claude Code short names. This article explains what our API does then.

Which model answers

A name that is not in the catalogue gives no error. We use our default coding model, `moonshotai/kimi-k2.7-code`, and Claude Code keeps working. The answer shows the name that was asked for. So Claude Code may say `claude-sonnet-...` when Kimi K2.7 Code was the one answering.

Agents are the exception: if the model is `agent/` followed by an id that does not exist or belongs to another account, the answer is `404 model_not_found`.

What you pay

You pay for `moonshotai/kimi-k2.7-code`, at its price. The price is in the **Models tab** and in `pricing`, in `GET /v1/models`. With the Coding Plan, it spends points, because this model is part of the plan.

Choosing the model for each function

Variable	What it chooses
`ANTHROPIC_MODEL`	The main model of the session. Always set it.
`ANTHROPIC_DEFAULT_SONNET_MODEL`	The model for the `sonnet` short name.
`ANTHROPIC_DEFAULT_OPUS_MODEL`	The model for the `opus` short name.
`ANTHROPIC_DEFAULT_HAIKU_MODEL`	The model for the `haiku` short name and for background tasks.
`CLAUDE_CODE_SUBAGENT_MODEL`	The model for subagents that have no other model set.

The values are catalogue ids, with the slash. The last four come from the Claude Code documentation. An example:

```
export ANTHROPIC_MODEL="moonshotai/kimi-k2.7-code"
export ANTHROPIC_DEFAULT_SONNET_MODEL="moonshotai/kimi-k2.7-code"
export ANTHROPIC_DEFAULT_OPUS_MODEL="deepseek-ai/deepseek-v4-pro"
export ANTHROPIC_DEFAULT_HAIKU_MODEL="deepseek-ai/deepseek-v4-flash"
```

Checking

`/status` shows the session model. If it shows a Claude Code name instead of the catalogue id, `ANTHROPIC_MODEL` is missing or the terminal did not read it. Open a new terminal and start Claude Code again.

Want to see the price first? `GET /v1/models?type=text&q=kimi` returns the model with its `pricing`. Listing the models spends no credits.

RECOMMENDED

Want to code with AI in Claude Code? Visit the Coding with AI page.

See Coding with AI →

SEE ALSO

- **Using Claude Code with All in One AI: the variables, the model and common errors**
- **The model for background tasks in Claude Code: ANTHROPIC_DEFAULT_HAIKU_MODEL**
- **Changing the model during a Claude Code session with /model**
- **Coding Plan: which plan to choose, what it costs and how to subscribe**
- **Coding with AI in All in One AI**

interweb

Interweb Mozambique

RLX Holdings, S.A. · Group RLX Holdings

TAX ID (NUIT)	401 191 607
LEGAL ENTITY NO. (NUEL)	105 045 974
ECONOMIC ACTIVITY CODE (CAE)	62022
REGISTERED OFFICE	Bairro 7 de Setembro Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique
CONTACT	info@interweb.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.interweb.co.mz
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-MZ-KB-3118 · v2026.11.28 · Generated on 28/11/2026 22:13