interweb

Generated on 28/11/2026 22:16

KNOWLEDGE BASE · PUBLIC DOCUMENT

Codex on Windows: saving the key with setx and opening a new terminal

Codex CLI

CODE	VERSION	COUNTRY · LANGUAGE
RLX-MZ-KB-3144	v2026.11.28	Mozambique · English

Interweb Mozambique
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.interweb.co.mz/knowledgebase/3144

Codex on Windows: saving the key with setx and opening a new terminal

Codex CLI Created on **November 28, 2026** 2 min read



On Windows, the step that fails most is the key. `setx` saves the variable, but only the windows opened afterwards see it. This article shows the whole path, from PowerShell to the first answer.

1. Install Codex

The official README gives, in PowerShell:

```
powershell -ExecutionPolicy ByPass -c "irm https://chatgpt.com/codex/install.ps1 | iex"
```

If you already have Node.js, you can also use `npm install -g @openai/codex`.

2. Save the key with setx

```
setx INTERWEB_API_KEY "prod_..."
```

`setx` saves the variable in your Windows account. The window where you typed it does not get it: only the ones you open next.

3. Close and reopen

1. Close the PowerShell or Command Prompt window where you ran `setx`.
2. If you use the VS Code terminal, close VS Code completely: its terminals inherit the variables from when VS Code started.
3. Open a new terminal and check that the variable exists, without showing it on screen.

In PowerShell:

```
if ($env:INTERWEB_API_KEY) { "OK" } else { "missing" }
```

In Command Prompt:

```
if defined INTERWEB_API_KEY (echo OK) else (echo missing)
```

4. The config.toml file

The file goes in `%USERPROFILE%\.codex\config.toml`. In PowerShell:

```
New-Item -ItemType Directory -Force "$HOME\.codex"
notepad "$HOME\.codex\config.toml"
```

Paste the configuration from **Codex CLI with All in One AI** and save. If you use **Save as**, choose **All files (*.*)**: otherwise Windows adds `.txt` to the name and Codex does not read the file.

For one window only

To test without saving anything, set the variable in the open terminal only. When you close the window, the variable is gone. In PowerShell:

```
$env:INTERWEB_API_KEY = "prod_..."
```

In Command Prompt:

```
set INTERWEB_API_KEY=prod_...
```

Changed your key?
Run `setx` again with the new key and open a new terminal. The old window keeps the old key, and a revoked key gives `401`.

RECOMMENDED

Want to code with AI in Codex? Visit the Coding with AI page.

See Coding with AI →

SEE ALSO

- **Codex CLI with All in One AI: creating config.toml, the key and the model** →
- **env_key in Codex: how it reads your key from an environment variable** →

Errors in Codex CLI: the OpenAI format and the code field

An API key or token has leaked: what to do, in the right order

Coding with AI in All in One AI

interweb

Interweb Mozambique

RLX Holdings, S.A. · Group RLX Holdings

TAX ID (NUIT)	401 191 607
LEGAL ENTITY NO. (NUEL)	105 045 974
ECONOMIC ACTIVITY CODE (CAE)	62022
REGISTERED OFFICE	Bairro 7 de Setembro Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique
CONTACT	info@interweb.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.interweb.co.mz
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-MZ-KB-3144 · v2026.11.28 · Generated on 28/11/2026 22:16