interweb

Generated on 28/11/2026 22:17

KNOWLEDGE BASE · PUBLIC DOCUMENT

# Why your Cursor requests go through Cursor's servers first

Cursor

| CODE | VERSION | COUNTRY · LANGUAGE |
| --- | --- | --- |
| RLX-MZ-KB-3146 | v2026.11.28 | Mozambique · English |

**Interweb Mozambique**
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.interweb.co.mz/knowledgebase/3146

# Why your Cursor requests go through Cursor's servers first

Cursor Created on **November 28, 2026** 2 min read



When you use your Interweb key in Cursor, the request does not go straight from your computer to our API. It goes through Cursor's servers first, which build the final request, and only then reaches us. This changes how you should create the key you use in Cursor.

## What Cursor says

According to **Cursor's help page on your own keys**, all requests are routed through Cursor's servers for final prompt building. The same page says the key is not stored on Cursor's servers and is not kept after the request is complete.

So each request travels like this: Cursor on your computer, Cursor's servers, and our API at `https://api.interweb.co.mz/v1`. The answer goes back the same way.

## The key's IP list

When you create a key, you can fill in an IP list: the key then only works from those addresses. With Cursor, the request reaches us from the address of Cursor's servers, not from yours. If the list only has your computer's or your office's IP, the API answers `403 ip_not_allowed`.

For Cursor, use a key without an IP list. The fields are in **how to create an API key**.

## A key just for Cursor

1. In the **API Center**, create a key named "Cursor" with only the `ai:read` and `ai:write` permissions. The chat needs nothing else.
2. Leave the IP list empty, for the reason above.
3. Pick a validity: 30, 90 or 365 days. When it ends, create another one and swap it in Cursor.

That way, if you need to cut Cursor's access, you revoke only this key and your other programs keep working. In History, the key filter shows only what Cursor spent.

## What goes through Cursor

The text of each request, with the code Cursor adds to the conversation, goes through Cursor's servers before it reaches us. On that part of the way, Cursor's privacy rules apply. If that does not suit your project, use a tool that runs on your computer and calls our address directly, such as Cline, OpenCode or Aider. See **which tool to choose**.

**If the Cursor key is exposed, revoke it straight away.**
See **what to do, in the right order**.

RECOMMENDED

Want our models in Cursor? Visit the Coding with AI page.

**See Coding with AI →**

SEE ALSO

- **Cursor with All in One AI: your key, our address and the models to add**
- **Cursor errors: 401, model not found and the /v1 address**
- **What Cursor spends: following its requests in the History tab**
- **Which coding tool to use with All in One AI: OpenCode, Claude Code, Codex, Cursor, Cline, Kilo Code or Aider**
- **Coding with AI in All in One AI**

interweb

## Interweb Mozambique

**RLX Holdings, S.A. · Group RLX Holdings**

| | |
|---|---|
| TAX ID (NUIT) | 401 191 607 |
| LEGAL ENTITY NO. (NUEL) | 105 045 974 |
| ECONOMIC ACTIVITY CODE (CAE) | 62022 |
| REGISTERED OFFICE | Bairro 7 de Setembro<br>Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique |
| CONTACT | info@interweb.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.interweb.co.mz |
| OPENING HOURS | Monday to Friday - 08 AM to 04 PM<br>Saturday & Sunday - Closed |

Online version of this document

RLX-MZ-KB-3146 · v2026.11.28 · Generated on 28/11/2026 22:17