interweb

Generated on 28/11/2026 22:20

KNOWLEDGE BASE · PUBLIC DOCUMENT

Adding more models to OpenCode: the models block and the id with the slash

OpenCode

CODE
RLX-MZ-KB-3186

VERSION
v2026.11.28


COUNTRY · LANGUAGE
Mozambique · English

Interweb Mozambique
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.interweb.co.mz/knowledgebase/3186

Adding more models to OpenCode: the models block and the id with the slash

OpenCode Created on **November 28, 2026** 3 min read



For your own provider, OpenCode only shows the models written in the `models` block of the file. To have another All in One AI model in `/models`, add a line for it. Here is how, without breaking the JSON.

What a line looks like

```
"zai-org/glm-5.2": { "name": "GLM 5.2", "limit": { "context": 1048576, "output": 16000 } }
```

Part	What it is
`"zai-org/glm-5.2"`	The catalogue id, exactly as it is, with the slash. This is what goes to our API.
`name`	The name you see in `/models`. You can write anything you like.
`limit`	The context and the maximum per answer. They are explained in **context and output limits in OpenCode**.

Adding the line

1. Open the file: the global one or the project one.
2. Find `"models"`, inside the Interweb provider.
3. Put a comma at the end of the last line in it and paste the new line below. If the new one is the last, it has no comma.

4 Save, close OpenCode and open it again. Type `/models` and choose the new model.

The block ends up like this, with four models:

```
"models": {
        "moonshotai/kimi-k2.7-code": { "name": "Kimi K2.7 Code", "limit": { "context": 262144, "output": 16000 } },
            "deepseek-ai/deepseek-v4-pro": { "name": "DeepSeek V4 Pro", "limit": { "context": 1048576, "output": 16000 } },
            "zai-org/glm-5.2": { "name": "GLM 5.2", "limit": { "context": 1048576, "output": 16000 } },
          "deepseek-ai/deepseek-v4-flash": { "name": "DeepSeek V4 Flash", "limit": { "context": 1048576, "output": 16000 } }
}
```

In a `.jsonc` file, a comma after the last item is accepted. In a `.json` file it is not, and OpenCode does not read the file.

The id with the slash

Every catalogue id has a slash, such as `moonshotai/kimi-k2.7-code`. In `models`, write it whole. Without the first part (just `kimi-k2.7-code`), the API answers `404 model_not_found`.

To choose the model, OpenCode puts the provider in front: `api/moonshotai/kimi-k2.7-code`. It cuts at the first slash. What comes before is the provider; the rest is the model, with its own slash. Capital letters count, so copy the ids exactly as they are.

The ids are in the Models tab of **All in One AI** or in the API list. On Linux and macOS:

```
curl "https://api.interweb.co.mz/v1/models?type=text" -H "Authorization: Bearer $INTERWEB_API_KEY"
```

In Windows PowerShell:

```
curl.exe "https://api.interweb.co.mz/v1/models?type=text" -H "Authorization: Bearer $env:INTERWEB_API_KEY"
```

Each model comes with its `id` (always with the slash), its `context_length` and its price in `pricing`. Listing the models spends no credits.

Which models to add

Use text models that support tools (function calling). OpenCode needs them to edit files and run commands:

Model	Context	What for
`moonshotai/kimi-k2.7-code`	262,144 tokens	Built for coding: the starting point for everyday work.
`deepseek-ai/deepseek-v4-pro`	1,048,576 tokens	Strong reasoning, for big changes and hard bugs.
`zai-org/glm-5.2`	1,048,576 tokens	Made for agents: handles tools well in long tasks.
`deepseek-ai/deepseek-v4-flash`	1,048,576 tokens	Fast and cheap, for background tasks and short questions.

The block in **OpenCode with All in One AI** already has the 79 models that support tools, from the most expensive to the cheapest. You can copy it whole and delete the lines you do not use. The price of each model is in the Models tab of **All in One AI**.

RECOMMENDED

Want more models in OpenCode? Visit the Coding with AI page.

See Coding with AI →

SEE ALSO

- **OpenCode with All in One AI: creating opencode.json from scratch, the key and the models**
- **Choosing the model in OpenCode: /models and the provider/model format**
- **Context and output limits in OpenCode: limit.context and limit.output**
- **Errors when setting up a tool with All in One AI: 401, model not found, no credits, /v1 and rejected config files**
- **Coding with AI in All in One AI**

interweb

Interweb Mozambique

RLX Holdings, S.A. · Group RLX Holdings

TAX ID (NUIT)	401 191 607
LEGAL ENTITY NO. (NUEL)	105 045 974
ECONOMIC ACTIVITY CODE (CAE)	62022
REGISTERED OFFICE	Bairro 7 de Setembro Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique
CONTACT	info@interweb.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.interweb.co.mz
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-MZ-KB-3186 · v2026.11.28 · Generated on 28/11/2026 22:20